

ECO-DRIVE SAE 5W-30 C4

ECO-DRIVE SAE 5W-30 C4 is a HC-synthetic high-performance low-friction engine oil with low sulphur, ash and phosphorus content (low-SAP). Base oils produced with the latest HC-synthesis technology and carefully chosen high-performance additives help reduce the sulphated ash content and guarantee reliable wear protection and keep the engine clean. Excellent cold start behaviour ensures optimum lubrication during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures.

ECO-DRIVE SAE 5W-30 C4 is recommended for use under all operating conditions and helps protect the environment as it reduces harmful emissions.

ECO-DRIVE SAE 5W-30 C4 has been specially developed for use in Renault diesel engines with particle filter (DPF). Do not use in 2.2dCi / G9T engines!

ECO-DRIVE SAE 5W-30 C4 prolongs the service life of the exhaust gas aftertreatment system and enhances its performance.

Specification

ACEA C4

Recommended application

Renault RN 0720 MB 226.51

Technical data	Unit	Test according	ECO-DRIVE SAE 5W-30 C4
density at 15°C	Kg/m³	DIN EN ISO 12185	852
Flammable COC	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm²/s	DIN 51562-1	70
Viscosity 100°C	mm²/s	DIN 51562-1	12
VI		DIN ISO 2909	162
TBN	mgKOH/g	DIN ISO 3771	7,3
Viscosity -30°C	mm²/s	DIN 51562-1	5750

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

