PRODUCT INFORMATION



EUROLUB MULTITEC FO 0W-30

Description **Applications:**

This fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Very suitable for Ford engines where the specification Ford WSS-M2C950-A with the viscosity SAE 0W-30 is prescribed.

Can be used with:	ACEA C2		
	Ford WSS-M2C950-A		
	Jaguar Land Rover STJLR.03.5007		

Delivery:	ArtNr. 319001	12 x 1 Liter	bottle
	ArtNr. 319005	4 x 5 Liter	can
	ArtNr. 319020	20 Liter	can
	ArtNr. 319060	60 Liter	hobbock
	ArtNr. 319208	208 Liter	drum
	ArtNr. 319100	Container	IBC

Technical Data:					
Data	Unit	Method	EUROLUB MULTITEC FO 0W-30		
Density at 15°C	kg/L	D 4052	0,843		
Viscosity at 40°C	cSt	D 445	44,2		
Viscosity at 100°C	cSt	D 445	9,4		
Viscosityindex (VI)		D 2270	203		
Flash point (COC)	°C	D 92	230		
Pourpoint	°C	D 6892	-42		

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com, info@eurolub.com

Druckdatum: 10.08.2021, erstellt am 22.10.2018 Referenz: R20150, 28.06.2018 Name: 319xxx_TDS_EN

Seite 1 von 1