

ECO-DRIVE LONGLIFE 3 SAE 5W-30

ECO-DRIVE LONGLIFE 3 SAE 5W-30 is a HC-synthetic high-performance low-friction oil for petrol and diesel engines in passenger cars. The oil is a low-SAP product with reduced sulphur, ash and phosphorus content. Base oils produced with the latest synthesis technology and carefully chosen innovative high-performance additives help reduce the sulphated ash content and guarantee reliable wear protection and keep the engine clean. Excellent cold start behaviour ensures optimum lubrication during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures. ECO-DRIVE LONGLIFE 3 SAE 5W-30 is recommended for use under all operating conditions and helps protect the environment as it reduces harmful emissions. ECO-DRIVE LONGLIFE 3 SAE 5W-30 has been specially designed for modern passenger car engines.

It is particularly recommended for BMW, Mercedes-Benz and VW/Audi engines with exhaust gas aftertreatment systems. ECO-DRIVE LONGLIFE 3 SAE 5W-30 prolongs the service life of the exhaust aftertreatment system and enhances its performance.

Specification

ACEA C3

Recommended application

VW 504 00 / 507 00 MB 229.51 BMW Longlife-04 Porsche C30

Technical data	Unit	Test according	ECO-DRIVE LONGLIFE 3 SAE 5W-30
density at 15°C	Kg/m³	DIN EN ISO 12185	852
Flammable COC	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-45
Viscosity 40°C	mm²/s	DIN 51562-1	70,1
Viscosity 100°C	mm²/s	DIN 51562-1	11,9
VI		DIN ISO 2909	167
TBN	mgKOH/g	DIN ISO 3771	6,2

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by Quality.

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com **PROFI-CAR** is a international trademark of **PROFI-TECH GmbH**