

EUROLUB Synt PDI SAE 5W/40

Description / Applications:	This universal motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application.
------------------------------------	--

Can be used with:	ACEA C3 API SN / CF MB 229.51 / 229.31 VW 505.00 / 505.01 BMW Longlife-04 GM dexos2™ Ford WSS-M2C-917-A Renault RN0700 / RN0710 Porsche A40
--------------------------	---

Delivery:	Art.-Nr. 308001	12 x 1 Liter	bottle
	Art.-Nr. 308005	4 x 5 Liter	can
	Art.-Nr. 308020	20 Liter	can
	Art.-Nr. 308060	60 Liter	hobbock
	Art.-Nr. 308208	208 Liter	drum
	Art.-Nr. 308100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Synt PDI SAE 5W/40
Density at 15°C	kg/L	D 4052	0,848
Viscosity at 40°C	cSt	D 445	93,89
Viscosity at 100°C	cSt	D 445	15,20
Viscosityindex (VI)		D 2270	171
Flash point (COC)	°C	D 92	230
Pourpoint	°C	D 6892	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com , info@eurolub.com	print: 10.09.2019, made 04.06.2018
	Referenz: R20365, 25.07.2019
	Name: Synt PDI SAE 5W-40 PDS_english_308xxx
	Seite 1 von 1