

## **ECO-DRIVE LONGLIFE 4 SAE OW-20**

ECO-DRIVE LONGLIFE 4 SAE 0W-20 is a synthetic high-performance low-friction engine oil for VW engines. Its special formulation guarantees highest thermal and mechanical stability while minimizing evaporation.

ECO-DRIVE LONGLIFE 4 SAE 0W-20 provides excellent wear protection and has outstanding low-temperature properties. This means that the oil is quickly distributed to all lube points and cold start wear is minimised. The highly effective dispersing additives prevent deposits on pistons and injection valves.

ECO-DRIVE LONGLIFE 4 SAE 0W-20 has been specially developed for use in VW and Audi engines of the latest generation with VW specifications 508 00 and 509 00.

This product is not backward compatible with VW 504 00 / 507 00 and other VW specifications.

## **Specification**

## **Recommended application**

VW 508 00 / 509 00 VW TL 525 77

| Technical data  | Unit    | Test according   | ECO-DRIVE LONGLIFE 4 SAE OW-20 |
|-----------------|---------|------------------|--------------------------------|
| density at 15°C | Kg/m³   | DIN EN ISO 12185 | 836                            |
| Flammable COC   | °C      | DIN ISO 2592     | 234                            |
| Pourpoint       | °C      | DIN ISO 3016     | -54                            |
| Viscosity 40°C  | mm²/s   | DIN 51562-1      |                                |
| Viscosity 100°C | mm²/s   | DIN 51562-1      | 8,1                            |
| VI              |         | DIN ISO 2909     | 174                            |
| TBN             | mgKOH/g | DIN ISO 3771     | 8                              |
| Viscosity -30°C | mm²/s   | DIN 51562-1      |                                |

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

