

EUROLUB SUPER ECO 0W-20



Description / Applications:	<p>SUPER ECO 0W-20 is a modern, synthetic, fuel economic motor oil based on special selected synthetic base oils with a high viscosity index and a well-balanced choice of advanced additives to obtain the following properties:</p> <ul style="list-style-type: none"> • A lower fuel consumption • A high and very stable viscosity index • A high resistance against shearing • A very fast cold start • A very good detergency and dispersion • A very strong protection against wear, corrosion and foaming 		
Can be used with:	<p>ACEA C5 API SP RC, API SN Plus RC ILSAC GF-5/-6A BMW Longlife-17 FE+ MB 229.71 Ford WSS-M2C947-B1 GM dexosD Opel/Vauxhall OV0401547 Volvo VCC RBS0-2AE Chrysler MS-12145 Fiat 9.55535-GSX</p>		
Delivery:	Art.-Nr. 226001	12 x 1 Liter	bottle
	Art.-Nr. 226004	4 x 4 Liter	can
	Art.-Nr. 226005	4 x 5 Liter	can
	Art.-Nr. 226020	20 Liter	can
	Art.-Nr. 226060	60 Liter	hobbock
	Art.-Nr. 226208	208 Liter	drum
	Art.-Nr. 226100	Container	IBC

*Keep in mind manufacturers instructions.

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB SUPER ECO 0W-20
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	41,6
Viscosity at 100°C	cSt	D 445	8,3
Viscosityindex (VI)		D 2270	179
Flash point (COC)	°C	D 92	222
Pourpoint	°C	D 6892	-51

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.