

EUROLUB Cleantec („Mid SAPS“) SAE 5W/30

Description/Applications:	This motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. Moreover this lubricant is also very suitable for passenger car diesel engines with pump-injector-unit. This product meets the requirements of several OEM's and thus has a wide application. Cleantec SAE 5W/30 is also suitable for KIA and Hyundai where the Specifications below are requested. The operating instructions of the vehicle and engine manufactures must be followed.
----------------------------------	--

Can be used with:	ACEA C2 / C3 API SN / CF VW 502.00 VW 505.00/505.01 MB 229.51 / MB 229.52 BMW Longlife-04 GM dexos2™
--------------------------	--

Delivery:	Art.-Nr. 349001	12 x 1 Liter	bottle
	Art.-Nr. 349005	4 x 5 Liter	can
	Art.-Nr. 349020	20 Liter	can
	Art.-Nr. 349060	60 Liter	hobbock
	Art.-Nr. 349208	208 Liter	drum
	Art.-Nr. 349100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB Cleantec 5W/30
Density at 15°C	kg/L	D 4052	0,848
Viscosity at 40°C	cSt	D 445	69,47
Viscosity at 100°C	cSt	D 445	11,82
Viscosityindex (VI)		D 2270	167
Flash point (COC)	°C	D 92	>220
Pourpoint	°C	D 6892	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.