

EUROLUB SYNT 5W-40

Description/Applications:	High performance engine oil of the generation, specially designed to meet the strict requirements of manufacturers and composed of non-conventional base oils and highquality additives. These provide an excellent fluidity at low temperatures, a very low resistance when starting, an exceptional viscosity index and a very high thermal stability. This oil is used in diesel engines of passenger cars with turbo and direct fuel injection.
----------------------------------	---

Can be used with:	ACEA A3 / B4 API SN / CF VW 502.00 / 505.00 MB 229.3 / 226.5 BMW Longlife-01 Porsche A40 Renault RN0700 / RN0710 GM LL-B-025 Fiat 9.55535-M2 PSA B71 2296
--------------------------	--

Delivery:	Art.-Nr. 316001	12 x 1 Liter	bottle
	Art.-Nr. 316004	4 x 4 Liter	can
	Art.-Nr. 316005	4 x 5 Liter	can
	Art.-Nr. 316020	20 Liter	can
	Art.-Nr. 316060	60 Liter	hobbock
	Art.-Nr. 316208	208 Liter	drum
	Art.-Nr. 316100	Container	IBC

PRODUCT INFORMATION



Technical Data:

Data	Unit	Method	EUROLUB SYNT 5W-40
Density at 15°C	kg/L	D 4052	0,849
Viscosity at 40°C	cSt	D 445	85,7
Viscosity at 100°C	cSt	D 445	14,4
Viscosityindex (VI)		D 2270	175
Flash point (COC)	°C	D 92	240
Pourpoint	°C	D 6892	-36

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.