PRODUCT INFORMATION



EUROLUB Cleanpower C1 SAE 5W/30

Description / Applications:

A universal, fuel economy, specially composed motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: These oils have the lowest SAPS limits and may be unsuitable for use in some engines.

Can be used with:	ACEA C1
-------------------	---------

Ford WSS-M2C934-B

Jaguar Land Rover STJLR.03.5005

JASO DL-1 Mazda

Delivery:	ArtNr. 213001	12 x 1 Liter	bottle	
	ArtNr. 213005	4 x 5 Liter	can	
	ArtNr. 213020	20 Liter	can	
	ArtNr. 213060	60 Liter	hobbock	
	ArtNr. 213208	208 Liter	drum	
	ArtNr. 213100	Container	IBC	

Technical Data:				
Data	Unit	Method	EUROLUB Cleanpower C1 SAE 5W/30	
Density at 15°C	kg/L	D 4052	0,845	
Viscosity at 40°C	cSt	D 445	58,4	
Viscosity at 100°C	cSt	D 445	10,1	
Viscosityindex (VI)		D 2270	161	
Flash point (COC)	°C	D 92	238	
Pourpoint	°C	D 6892	-35	

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49(0)8165 / 95 91 - 0, Fax +49(0)8165 / 95 91 - 20 www.eurolub.com, info@eurolub.com print: 10.09.2019, erstellt am 20.11.2018

Referenz: R20109, 17.08.2018

Name: Cleanpower C1 SAE 5W-30 PDS_english_213xxx

Seite 1 von 1