

EUROLUB KÜHLERSCHUTZ ANF

Description/Applications:	<p>KÜHLERSCHUTZ ANF is a nitrite, amine and phosphate free antifreeze based on ethylene glycol (MEG=mono ethylene ethanediol). Suitable for summer and winter with rust and frost protection. It is distinguished by its special corrosion protection additives for gray cast iron or aluminum motors suitable not foam and behaves neutrally to metals, rubber parts and seals.</p> <p>KÜHLERSCHUTZ ANF must be diluted with water before use. It is hard water compatible and can be mixed with tap water(*) before filling into the cooling system to give solutions in the concentration range of 30 to 50 % by volume.</p> <p>(*)= For preparation of the coolant use clean, not overly hard water. Waste water from mining, sea water, brackish water, brine, industrial waste water are all unsuitable.</p>
----------------------------------	--

Can be used with:	<p>BS 6580 AFNOR NF R15-601 AS 2108 ASTM 3306 CUNA NC 956-16 SAE J 1034 UNE 26-361</p>
--------------------------	--

Delivery:	<table> <tr> <td>Art.-Nr. 820015</td> <td>12 x 1 Liter</td> <td>bottle</td> </tr> <tr> <td>Art.-Nr. 820005</td> <td>4 x 5 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 820020</td> <td>20 Liter</td> <td>can</td> </tr> <tr> <td>Art.-Nr. 820060</td> <td>60 Liter</td> <td>hobbock</td> </tr> <tr> <td>Art.-Nr. 820208</td> <td>208 Liter</td> <td>drum</td> </tr> <tr> <td>Art.-Nr. 820100</td> <td>Container</td> <td>IBC</td> </tr> </table>	Art.-Nr. 820015	12 x 1 Liter	bottle	Art.-Nr. 820005	4 x 5 Liter	can	Art.-Nr. 820020	20 Liter	can	Art.-Nr. 820060	60 Liter	hobbock	Art.-Nr. 820208	208 Liter	drum	Art.-Nr. 820100	Container	IBC
Art.-Nr. 820015	12 x 1 Liter	bottle																	
Art.-Nr. 820005	4 x 5 Liter	can																	
Art.-Nr. 820020	20 Liter	can																	
Art.-Nr. 820060	60 Liter	hobbock																	
Art.-Nr. 820208	208 Liter	drum																	
Art.-Nr. 820100	Container	IBC																	

PRODUCT INFORMATION



Water mixtures:

(Do not mix below -20 ° C, since less than 33% Antifreeze no corrosion protection is guaranteed.)

Ratio antifreeze	Ratio water	Frost protection to:
1 part	2 parts	-20°C
1 part	1,5 parts	-27°C
1 part	1 part	-37°C

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.