PRODUCT INFORMATION



EUROLUB AdBlue®

For exhaust aftertreatment of automotive diesel engines with SCR-technology.

Discription:	High-purity urea solution for SCR exhaust aftertreatment / AUS 32 acc.			
Application:	ISO 22241.			
	Application: Do not fill in the fuel tank or other liquid containers of the			
	vehicle, but only in the designated and separate AdBlue® tank!			
	AdBlue® is a registered trademark of the Association of the Automotive			
	Industrie e.V. (VDA).			

Product feature:	Recommended storage temperature between 0 ° C and + 30 ° C.
Storage:	Avoid direct sunlight.
	If not used, seal AdBlue® containers airtight.
	AdBlue® can freeze at -11 ° C. Therefore, it is important that you use a
	storage location where the temperature can not drop below this level. If
	AdBlue® is frozen, it can be reused after thawing as it returns to its
	original state.
	If the instructions for storage are followed correctly, AdBlue can be
	stored for up to one year.

Can be used with:	AUS 32 gem. ISO 22241
	Audi G 052 910 A4
	BMW 83 19 0 441 139
	EVOBUS 004 989 04 20
	MB 004 989 04 20
	Seat G 052 910 A4
	Setra 004 989 04 20
	Skoda G 052 910 A4
	VW G 052 910 A4

Delivery:	ArtNr. 845005	4 x 5 Liter can VPE palett = 96 x 5 Liter	
	ArtNr. 845010	10 Liter can VPE palett = 60 x 10 Liter	
	ArtNr. 845020	20 Liter can VPE palett = 39 x 20 Liter	
	ArtNr. 845060	60 Liter drum VPE palett = 16 x 60 Liter	
	ArtNr. 845208	208 Liter drum VPE palett 2 x 208 Liter	
	ArtNr. 845100	1.000 IBC	

The specified data can make changes. Observe the operating instructions of the manufacturer. Conditional data changes reserved. This information is intended to describe the product and is not intended to assert certain characteristics. A liability can not be derived from this.