



DIESEL-POWER-TRUCK TURBO SAE 20W-50

DIESEL-POWER-TRUCK TURBO SAE 20W-50 is a multi-grade engine oil designed for year-round use. Engines with turbocharger and charge air cooling require oils that can withstand higher thermal and mechanical loads. DIESEL-POWER-TRUCK TURBO SAE 20W-50 meets the requirements for such demanding operating conditions even at extended oil change intervals. It ensures reliable cold start at low ambient temperatures and proper lubrication at high operating temperatures. Thanks to the use of shear-resistant active agents, the product retains its SAE class 20W-50 properties over the entire oil change interval. DIESEL-POWER-TRUCK TURBO SAE 20W-50 is used in heavy-duty commercial and passenger cars with diesel engines, and in vehicles with petrol engines. Engine oils of this class are generally recommended where oil change intervals are extended.

Specification

ACEA E7, A4/B4

API CI-4 / SL

JASO DH-1

Recommended application

MB 228.3 / 229.1

MAN 3275-1

Volvo VDS-2

Cummins CES 20076 / 77 / 78

Deutz DQC II-10

Detroit Diesel DDC 93K215

Technical data	Unit	Test according	DIESEL-POWER-TRUCK TURBO SAE 20W-50
density at 15°C	Kg/m ³	DIN EN ISO 12185	882
Flammable COC	°C	DIN ISO 2592	> 210
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm ² /s	DIN 51562-1	142
Viscosity 100°C	mm ² /s	DIN 51562-1	17,8
VI		DIN ISO 2909	139
TBN	mgKOH/g	DIN ISO 3771	11

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com

PROFI-CAR is a international trademark of **PROFI-TECH GmbH**