



performance SAE 20W-50

performance SAE 20W-50 is a mineral high-performance universal engine oil of viscosity class SAE 20W-50. Base oils produced with the latest refinery technology and carefully selected innovative additives guarantee that the product meets the highest requirements. Its outstanding properties include excellent lubrication safety at high temperatures and extreme wear protection under all operating conditions. Cleansing additives prevent deposits, but the pistons and valves remain clean. The formation of black mud is prevented. Engine cleanliness and low friction reduce energy losses and reduce maintenance costs. performance SAE 20W-50 is a powerful motor oil, universally applicable, even under high stress. The range of services covers the requirements of passenger car petrol and diesel engines with and without turbocharging. The high requirements of modern, low-consumption engines to meet the stricter emission standards are met with reserve.

Specification

ACEA A3/B4

API SJ/CF

Recommended application

Technical data	Unit	Test according	performance SAE 20W-50
density at 15°C	Kg/m ³	DIN EN ISO 12185	885
Flammable COC	°C	DIN ISO 2592	236
Pourpoint	°C	DIN ISO 3016	-36
Viscosity 40°C	mm ² /s	DIN 51562-1	157
Viscosity 100°C	mm ² /s	DIN 51562-1	18,4
VI		DIN ISO 2909	132
TBN	mgKOH/g	DIN ISO 3771	8,7

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**