



SYNTH-TECH XT SAE 5W-30

SYNTH-TECH XT SAE 5W-30 is a HC-synthetic high-performance low-friction engine oil for petrol passenger cars. Base oils made with the latest HC-synthesis technology and carefully chosen innovative low-phosphorus and low-sulphur additives are combined to produce a lubricant that exceeds today's requirements. Excellent cold start behaviour ensures optimum lubrication during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures. A special combination of active agents based on the latest technology that are specially chosen to match the synthetic components provides unrivalled protection against wear, deposits and black sludge while keeping the engine clean. As it significantly reduces the fuel consumption, SYNTH-TECH XT SAE 5W-30 helps protect the environment under reduction of emissions.

SYNTH-TECH XT SAE 5W-30 is particularly recommended for use in the latest petrol, ethanol (up to E85), propane and natural gas engines of passenger cars, CUV, SUV and vans during the whole year.

Specification

API SN

ILSAC GF-5

Recommended application

Technical data	Unit	Test according	SYNTH-TECH XT SAE 5W-30
density at 15°C	Kg/m ³	DIN EN ISO 12185	855
Flammable COC	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-40
Viscosity 40°C	mm ² /s	DIN 51562-1	62,3
Viscosity 100°C	mm ² /s	DIN 51562-1	10,7
VI		DIN ISO 2909	163
TBN	mgKOH/g	DIN ISO 3771	7,7
Viscosity -30°C	mm ² /s	DIN 51562-1	5500

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

powered by **Quality.**

PROFI-CAR
MADE IN GERMANY

PROFI-TECH GmbH • Otto-Lilienthal-Strasse 2 • 88046 Friedrichshafen, Germany
Tel.: +49 7541 40286-0 • Fax: +49 7541 40286-99 • www.profi-tech.com • info@profi-tech.com
PROFI-CAR is a international trademark of **PROFI-TECH GmbH**